

SPP

Soportes pasacables pequeños, simples, dobles y cuádruples

- Soportes pasacables para cables con cabeza de 2 a 16 mm de diámetro
- Disponible sin agujero
- Colores gris y negro
- UL94V0 para ambos colores



Los soportes pasacables de la serie SPP permiten acomodar una gama de cables de 2 a 16 mm de diámetro dentro de los marcos divisibles de la serie DES.

Las versiones 2X y 4X son adecuadas para aumentar el número de cables en los marcos.

Características

Material: Elastómero termoplástico (TPE)

Inflamabilidad: autoextinguible según UL94-V0 (gris o negro)



Temperatura: -40 °C... +110 °C (estática)

Propiedades: sin halógenos, sin siliconas

Productos relacionados

DES 24 DES L5 DES PRED
DES 16 DES L4 DES PRED 90

DES 10 DES L3 DES CLICK
DES Q DES L2



Modelo/ Código	Ø del cable [mm]	Modelo/ Código	Piezas x paq.
			
SPP-0G_MPX	“sin agujero”	SPP-0B_MPX	10
SPP-2G_MPX	2-3	SPP-2B_MPX	
SPP-3G_MPX	3-4	SPP-3B_MPX	
SPP-4G_MPX	4-5	SPP-4B_MPX	
SPP-5G_MPX	5-6	SPP-5B_MPX	
SPP-6G_MPX	6-7	SPP-6B_MPX	
SPP-7G_MPX	7-8	SPP-7B_MPX	
SPP-8G_MPX	8-9	SPP-8B_MPX	
SPP-9G_MPX	9-10	SPP-9B_MPX	
SPP-10G_MPX	10-11	SPP-10B_MPX	
SPP-11G_MPX	11-12	SPP-11B_MPX	
SPP-12G_MPX	12-13	SPP-12B_MPX	
SPP-13G_MPX	13-14	SPP-13B_MPX	
SPP-14G_MPX	14-15	SPP-14B_MPX	
SPP-15G_MPX	15-16	SPP-15B_MPX	
SPP-16G_MPX	16	SPP-16B_MPX	
			
SPP-2x2G_MPX	2X2	SPP-2x2B_MPX	10
SPP-2x3G_MPX	2X3	SPP-2x3B_MPX	
SPP-2x4G_MPX	2X4	SPP-2x4B_MPX	
SPP-2x5G_MPX	2X5	SPP-2x5B_MPX	
SPP-2x6G_MPX	2X6	SPP-2x6B_MPX	
SPP-2x7G_MPX	2X7	SPP-2x7B_MPX	
SPP-2x8G_MPX	2X8	SPP-2x8B_MPX	
			
SPP-4x2G_MPX	4X2	SPP-4x2B_MPX	10
SPP-4x3G_MPX	4X3	SPP-4x3B_MPX	
SPP-4x4G_MPX	4X4	SPP-4x4B_MPX	
SPP-4x5G_MPX	4X5	SPP-4x5B_MPX	
SPP-4x6G_MPX	4X6	SPP-4x6B_MPX	